

pureal

pure & real water

PUREAL Water Purifier Pure and Real Water





pico gram

Mission



PICOGRAM PHILOSOPHY



Talented Human Resources

+



Core Technology

>



Advanced service

+



Best Products

>



Contribution to the Region, Nation and Human Society

World Trade Mark

pureal

pure & real water



PUREAL BRAND STORY

Pure water



+

Real water





pureal

PUREAL Direct Water Purifier



Type	Stand type
Inlet Water	Tap Water Only
Flow Rate	Ambient: 2.0lpm (0.5 GPM)
Operating Pressure	0.7~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Weight	5 kg
Size(mm)	(W)115 x (D)436 x (H)341
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Slim Design



Replaceable tap



Quick change



No electricity





pureal

PUREAL Direct Premium Water Purifier



Type	Stand type
Inlet Water	Tap Water Only
Flow Rate	Ambient: 2.0LPM (0.5 GPM)
Operating Pressure	0.7~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Weight	5 kg
Size(mm)	(W)115 x (D)436 x (H)341
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Sediment & Carbon block filter 2nd stage : Electro positive membrane ACF filter 3rd stage : Silver carbon block with Heavy metal agent filter



Slim Design Replaceable tap Quick change No electricity






pureal

PUREAL Hydrogen Water Purifier



Type	Stand type
Inlet Water	Tap Water Only
Power	AC 100~240V, 50/60Hz
ORP level	- 400mV
Flow Rate	Hydrogen: 1.0LPM (0.25GPM) Ambient: 2.0LPM (0.5 GPM)
Operating Pressure	1.5~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Size(mm) / Weight	(W)115 x (D)436 x (H)341 / 6 kg
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Slim Design Replaceable tap Quick change Hydrogen Water





pureal

PUREAL Hot Water Purifier



Type	Stand type
Inlet Water	Tap Water Only
Power	AC 220~240V, 50/60Hz
Hot water temperature	Up to 85 °C
Flow Rate	Hot: 0.4 LPM (0.2 GPM) Ambient: 2.0LPM (0.5 GPM)
Operating Pressure	1.5~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Size(mm) / Weight	(W)115 x (D)436 x (H)341 / 6 kg
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Slim Design



Replaceable tap



Quick change



Hot Water





pureal

PUREAL Cold Water Purifier



Type	Stand type
Inlet Water	Tap Water Only
Power	AC 110~240V, 50/60Hz
Cold water Temperature	Below 10°C
Flow Rate	Ambient: 1.7LPM (0.45 GPM) Cold: 1.3LPM (0.34 GPM)
Operating Pressure	1.5~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Size(mm) / Weight	(W)185 x (D)490 x (H)445 / 14.5kg
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Instant Cooling System



Replaceable tap



Quick change



Energy Saving System





pureal



PUREAL Hot and Cold Water Purifier

Type	Stand type
Inlet Water	Tap Water Only
Power	AC 220~240V, 50/60Hz
Hot & Cold water Temperature	Hot: 40°C, 70°C, 80°C Cold: Below 10 °C
Flow Rate	Ambient: 1.7LPM (0.45 GPM) Hot: 0.4 LPM (0.2 GPM) Cold: 1.3LPM (0.34 GPM)
Operating Pressure	1.5~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Size(mm) / Weight	(W)185 x (D)490 x (H)445 / 14.5kg
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Hot & cold Water



Replaceable tap



Quick change



Energy Saving System





pureal

PUREAL UTS (Under The Sink) Water Purifier



Type	Under the sink
Inlet Water	Tap Water Only
Flow Rate	2.0LPM (0.5 GPM)
Operating Pressure	0.7~7 kgf/cm ²
Capacity	4 / 12 / 12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Weight	3 kg
Size(mm)	(W)97.5 x (D)226 x (H)252
Filter Size	8", (D)Φ66 X (L)197 mm
Filter Stages & type	3 stage / Easy Twist Type
Filter composition	1st stage : Composite Carbon Block filter 2nd stage : Electro Positive Membrane filter 3rd stage : Silver Carbon Block filter



Under the sink



Tankless



Quick change



No electricity



PUREAL UTS – EFRO (Eco Friendly Reverse Osmosis) Water Purifier

Type	Under the sink
Inlet Water	Tap Water Only
Power	AC 110~240V, 50/60Hz
Flow Rate	50 / 75 / 100 GPD
Capacity	6 / 6 / 24 / 12 months (Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Size(mm) / Weight	(W)386 x (D)160 x (H)414 / 16 kg
Filter Size	11", (D)Φ66 X (L)290 mm 13", (D)Φ66 X (L)325 mm
Filter Stages & type	4 stage / Easy Twist Type
Filter composition	1st stage : Sediment 2nd stage : Carbon Block 3rd stage : EFRO membrane (50 / 75 / 100GPD) – NSF 58 certified 4th stage : GAC (Granular Activated Carbon)



Under the sink Less brine water ECO-Friendly Quick change

pureal



PUREAL Maxstream Hybrid Commercial Water purifier

Type	Under the sink
Inlet Water	Tap Water Only
Flow Rate	6.0LPM (1.5 GPM)
Operating Pressure	0.7~7 kgf/cm ²
Capacity	12 months(Korean tap water condition)
Working Temperature	5~35°C
Material	PP, POM, ABS
Weight	4kg / 8kg
Size(mm)	1st stage : (W)187 x (D)135 x (H)496 2nd stage : (W)318 x (D)135 x (H)496
Filter Size	15", (D)Φ115 X (L)373 mm
Filter Stages & type	1 ~ 2 Stage (Parallel) / Easy Twist type
Filter composition	Sediment + Elector positive membrane + Carbon block + Scale inhibitor



Under the sink High Capacity Quick change No electricity





pureal

PUREAL Pitcher Water Purifier



Type	Pitcher type
Inlet Water	Tap Water Only
Flow Rate	0.2LPM
Capacity	40 days(Korean tap water condition)
Working Temperature	5~35°C
Material	SAN, ABS, PP (BPA-Free)
Weight	1.5 kg
Size(mm)	(W)170 x (D)250 x (H)270
Filter Size	100 X 57 X 78mm
Filter Stages & type	1 Stage / 2 Step
Filter composition	Granular Activated Carbon Ion exchange resin

1.5kg
Portable

\$
Economical

⚡
No electricity





pureal

PUREAL Vitamin Shower Filter



Type	Shower Filter
Working Temperature	5~50°C
Weight	150g (Vitamin gel 60g)
Capacity	25 ~ 40 days(Korean tap water condition)
Filter size	6 inch
Material	PP
Filter composition	Vitamin C, Milk powder, Arbutin Rose, Cherry blossom, Acacia, Strawberry scent



FDA Approved
Sediment Filter




Residual Chlorine
Removal



Vitamin-C

Installation



Shower head



Tap



pureal Premium Replacement Filter

- 1st stage : Composite Carbon Block filter
- 2nd stage : Electro Positive Membrane filter
- 3rd stage : Silver Carbon Block filter



pureal Replacement Filter

- 1st stage : Sediment & Carbon block filter
- 2nd stage : Electro positive membrane ACF filter
- 3rd stage : Silver carbon block with Heavy metal agent filter



pureal Sterilizing Filter set

NaDCC (Sodium dichloro isocyanurate)

